

DISTRIBUTED CONTEXT AWARE DYNAMIC ADAPTATION MODEL FOR KNOWLEDGE ASSESSMENT IN E-LEARNING SYSTEM

V.Geetha¹, S.Chandrasekaran², R.Nadarajan³, G.S.Nandakumar⁴

¹Department of Computer Applications, Kumaraguru College of Technology,

²Department of Computer Science & Engineering, Kumaraguru College of Technology,

³Department of Mathematics & Computer Applications, PSG College of Technology, Coimbatore,
Anna University, Chennai, India

Email: ¹geethasuresh@rediffmail.com

ABSTRACT

The objective of the work is to propose a context driven dynamic adaptation model for knowledge assessment in E-Learning system through software as component. Most of the existing models deployed for Knowledge Management have focused on the contents of the assessment while giving less emphasis to the context with which the assessment services are to be rendered. A timed automaton has been proposed to accept the user requests for services navigating through the different rules resulting in a change in the behavioral states. The various states are then rewritten according to the runtime policy of application incorporating the uncertainties pertaining to the nature of services, content, time and policy changes. This context driven approach considers the nature of the application and its content along with the run time policy of different applications. An architectural framework with dynamic adaptation model has been implemented using PHP and MySQL Server and extensive testing has been carried out. Interesting inferences have been observed in terms of the session time and rewriting rules.

Keywords: *Context-awareness, Dynamic Adaptation, Component Services, Timed Automaton, Architectural Framework, Degree of Toughness (DT), E-Assessment*

1.0 INTRODUCTION

Context awareness feature can be expressed in terms of location, time, environment and workspace in the decision making process. Context has been defined as “any information that can be used to characterize the situation of an entity” [1]. It can be classified with respect to the user as a novice, a savvy or an expert based on the nature of application. Adaptability deals with dynamically changing the functionalities of the computational entities in response to the changing operating conditions. Some of the examples of services which need quick and selective adaptation are gaming service, calculation request service, mailing service, E-learning, etc. Business services in the areas like healthcare, insurance and banking must be highly adaptable to meet the changing need of the customers. A brief overview of existing and relevant context aware architectures is presented below:

Bradley et al. [2] in their work have achieved context aware computing by representing the state of the system by a vector of feature values. The time, location and policy of the service provider are considered to determine the exact context based on which the adaptation engine starts with its predefined behavior. The adaptation module first identifies the current context that the learner is situated in, based on a number of variables which indicate the individual contextual factors like the physical address of the location, the type of location, and the time available in the work, as proposed by Jane et al.[3]. Tarak Chaari et al. [4] have proposed a new definition of context and established three dimensions for context namely services, content and presentation.

Most of the existing literatures on context aware system focus on the layered architecture. Anders et al. [5] have defined an adaptive context aware application with two levels and a simple response system using the context middleware as a complex and adaptive multiagent system. A layered context stack has been proposed by Wei Li [6] to collect, interpret, aggregate and analyze of sensor data to a useful high level context information. The parameters which constitute the context need not be considered on a single layer for computation purposes since some of the parameters have to be dealt only at the end session of the application. Hence, the concept of layered contexts comes to solve the un-timed occurrence of these parameters.

Mahmoud Hussein et al. [7] in their approach have proposed an adaptive context awareness model in which the context relationships are considered at the modeling level, thereby reducing the system development errors.

They have separated the functionality and the context management to reduce the system errors. Mare Dalmau et al. [8] have highlighted the importance of adding adaptation to the context which needs a well designed architecture that takes care of irrelevant and redundant information. Similar idea was proposed by Davy Peuveneers et al. [9] in a modular context management system, where the effect of removing unnecessary transformation and reasoning components were studied. The consistent program behavior ignoring context changes within the particular scope of the software system was considered in [10, 11]. Since context information is volatile, the composition of context dependent behavior is continuously subject to change.

In E-learning, there is a paradigm shift in assessment methodology from the conventional pen and paper based tests to a more dynamic interactive approach of adaptive tests. The goal is to provide a personalized learning experience tailored to the user's needs. The deployed E-assessment software services can be reused if and only if they are context sensitive and highly adaptable. The adaptability in E-Assessment takes into consideration the learner's situation and their personal characteristics in generating a personalized learning experience. It facilitates a user's request for the required services taking into consideration the different types of contexts. The abstraction level of context will vary since a context by itself may be a composite variable consisting of different contexts. In the case of knowledge assessment in E-learning, the context has been defined in terms of learner's state, educational activity state, the infrastructure state and the environmental state where the adaptation engine considers all the four states as input and produces educational activity as output according to Economides [12]. The various areas of orientation of Computer Adaptive Testing as given by Economides [13] are content, time, difficulty level, score, presentation, media and format, communication and collaboration, feedback, control examinee characteristic and educational outcomes. A new approach that refines the results of the assessment in computerized testing by exploring the user's knowledge has been proposed by Lamboudis et al. [14]. They have proposed an approach in which the system waits for the user to check the validity of an answer and then proceeds to the next question. An exploration module is called to allow the user to have a second chance to provide the validity of the answer. The depth of exploration is an implementation decision to be taken by the designer. The earlier work proposed by Jane et al. [15] described a generic Context Aware and Adaptive Learning schedule (CALS) for selecting the appropriate learning material for learners based on their preferences and contextual features. The tool consists of four logical layers namely learner model, learning preference adaptation, contextual feature adaptation and learning object selection. This can be used in concordance with other models as in [16].

The main focus of this research work is to propose a highly adaptable assessment service that can be deployed as distributed software in a knowledge management framework. All the requested software services are described once and deployed as software component or services; the completeness and correctness of the services are monitored continuously. The proposed model of context aware adaptation model identifies four dimensions for the context variable applicable to the assessment application through which the rules of adaptation are derived. The users may also request the same set of services periodically with different content in different contexts due to which the policy rules should be changed and rewritten. The basic underlying assumption in the proposed model is that the question selection time and total time are equal for all the users.

The organization of the paper is as follows: Section 2 identifies the critical dimensions of the context variable selected in E-Assessment; Section 3 proposes a distributed architecture for dynamic adaptation applicable to E-Assessment focusing on the context with which the questions are to be selected over different sessions. Section 4 deals with mechanism of the rules that are generated and rewritten for quick adaptation to increase the performance of the assessment with the help of the system behavior. Section 5 highlights the proposed adaptation model on the context driven web based assessment services in an E-Learning system. Section 6 discusses the related performance and metrics of adaptation in E-Assessment system. Section 7 concludes the work with its limitation on applicability and scalability centered on the nature of deployment and the assessment capacity of size.

2.0 CONTEXTS IN E-ASSESSMENT AND THEIR DIMENSIONS

The assessment of academic performance nowadays is not only based on the answering ability but also on the context where the question contents are thrown up. The dimension variables like time, content, the type of the application and the run time policy decisions play an important role in deciding the performance of context aware computing systems as shown in Fig 1. The proposed model focuses on the dynamic adaptation of the assessment service for different contexts based on the needs of different types of learners.




Fig. 1. Dimensions of knowledge assessment

The dimensions are also dependent on each other as far as a single context variable is considered. For example, in E-Assessment the percentage of questions correctly answered, the time taken for the test etc are some of the context variables in deciding the performance of the user whereas the gender, the knowledge of the user, their proficiency of the domain are some of the dimensions in that context. In web applications, each and every service may have a number of different contexts and each context may have multiple dimensions.

The number of components or services deployed in a typical application can be considered as a set of Co , the various context variables with which the application can be executed is treated as a set of Cx and the multiple dimensions of each context variable can be considered as the third set, Cd . The selection of the correct context variable is done by the adaptation engine based on rules to exploit the surjective functional mapping between the variables and the dimensions as shown in Fig 2.




Fig. 2. Triangular surjective functional mapping component, context and dimension

The application components can be a domain set and the context variables are co-domain with the dimensions as the range set. The functional mapping is to be modeled based on the application with the number of elements in each and every set and the binary relationships between them as mentioned below:

$$\begin{aligned}
 Co_1 &\longrightarrow Cx_1^1 \longrightarrow Cd_j^1 + Cd_j^2 + Cd_j^3 & (1) \\
 Co_2 &\longrightarrow Cx_2^2 \longrightarrow Cd_j^4 & (2) \\
 Co_3 &\longrightarrow Cx_3^3 \longrightarrow Cd_j^5 & (3) \\
 Co_4 &\longrightarrow Cx_4^4 \longrightarrow Cd_j^3 + Cd_j^5 & (4)
 \end{aligned}$$

For example, the first mapping conveys that the context in the application component Co_1 is one to one mapped with the context variable Cx_1^1 which in turn is connected with three dimensions Cd_1^1 , Cd_1^2 and Cd_1^3 of the same context Cx_1^1 .

3.0 DISTRIBUTED ARCHITECTURE FRAMEWORK WITH DYNAMIC ADAPTATION

The architectural framework for dynamic adaptation in E-Assessment is given in Fig 3. The knowledge assessment in an E-Learning system has to be adaptable to reflect the incoming changes from various external bodies like the government educational policies, standards of syllabus, regulations in the specified curriculum and evaluation policies at the user profile which govern the quality of the education system. This is handled by the run time policy detector. To incorporate the change of the hour and to take an intelligent decision in the system, a collaboration of many software component services are needed. The adaptation manager holds a database of rules required to perform adaptation on the application. It monitors significant context changes in the application according to the current context and user preferences and also takes care of rewriting the rules. The proposed framework incorporates the key process activities through the time management, content analyzer and the session allocator. The selection of the session allocation is based on the summary of report submitted by the adaptation manager. The decision making section of the application uses adaptation rules and the goal of the session allocator is to determine which tasks from the current context of the user should be scheduled to carry out the assessment procedure. During the execution of the application, the contents are analyzed with respect to the context to provide information to the service allocator. The umbrella activities like reporting and violation message display components are also to be considered to deliver the application as a real product. The correct message will be fed in the form of rules into the runtime policy generator. The proposed middleware component must then detect the events and activate the appropriate interfaces in the adaptation manager in the middleware.




Fig. 3. Distributed architecture framework for dynamic adaptation


The adaptation engine can be computationally represented by a non deterministic finite state automaton NDFA which can be realized and executed from the middleware component. The individual states and transitions are monitored in the respective functional blocks given as an extended timed automaton.

The system checks for the validity of the domain. If the domain is valid (exists *i* the database), the system checks the policy and starts the session if the policy holds good. The system begins with the analysis of the input patterns following which the adaptation rules are generated. The system continues with the adaptation procedure until the time duration of the assessment elapses or the questions for the prescribed marks have been attempted, whichever occurs first.


4.0 ADAPTATION RULES AND REWRITING

The performance of the proposed context aware online adaptation model for knowledge management depends on the sensitivity and selectivity of the application over its context changes. Since the application is inherently time sensitive, the time taken for the context and its dimension switch over should be minimum. To minimize the challenge of time constraint, a rewrite based technique is incorporated. The rules that are to be generated and rewritten can be realized as shown below:


Rule R: Get (user id, domain, time setting and choice level) from user as input. Then, the control goes to “store-domain” state shown in its behavioral automaton.




Rule S: This rule is meant for checking the validity of the selected domain. If the domain is valid i.e., found in domain listing, then the system moves to “wait” state, else to the previous “read” state.




Rule W: The system Finite State Machine (FSM) model waits for a specified period of time and goes to state “check policy”.




Rule C: The policy rules are checked and if there is a violation on the context or its dimension, the system model goes to state *R*. Else, the session begins and it goes to the state named , “analyze”.




Rule A: By this rule, the model enters into state of “analyze” based on the *DT* choice level and input given by the user for a specified number of times. Based on the policy rules, it moves to state *G*.




Rule G: New rules are generated based on the user choice and through implementing the generated rules , it goes to state *T* to check if the time of the test has elapsed. If the time has not elapsed, the rules are changed and also a check is made to ensure that the user has not attempted any other trial for the maximum prescribed marks.




Rule M: The time utilized so far is checked with the time duration of the test. If the time has elapsed, then it goes to State *T*. Otherwise it continues with the test with the new set of rules.



Rule T: Initiates the state *D*. Once reports are generated in *D*, the session ends.



Rule D: Generates the reports and goes to state *T*.



The rules which are the reflections of the policies for the acceptance of the user input, checks the validity and acts as per the run time inputs given by the users. The rule based system moves from one rule to another rule based on the input and context and tries to rewrite the same rules over different sessions but with different dimensions. The lists of attributes are stored as records in the MySQL database and the rules are coded in PHP.

5.0 E- ASSESSMENT STRATEGY AND IMPLEMENTATION

Assessing the performance using an evaluation strategy is an important part of E-learning. Adaptive testing is a form of computer-based assessment that adapts to the students’ ability level. The main objective of adaptive assessment is to conduct an optimal test for all the students. In conventional tests, the same sets of questions are administered to all the waste their time attempting questions which are either very trivial or very difficult to their ability. Students get frustrated when the difficulty of the questions is higher than their ability level and bored if it is lower than their ability. But in the procedure of adaptive testing, the questions will be generated based on the individual ability of the student. This will result in generating different sets of questions for different students, keeping their enthusiasm to face the test steadily. If the student gets correct answer for a question, the computer will then select the next question from a higher difficulty level; otherwise the next question will be from a lower difficulty level. Students proficiency in a subject will be assessed with a fewer questions than in conventional tests. A finer discrimination in all ranges of performance is possible in adaptive strategy. This will improve the effectiveness of the assessment. An adaptation model on the context driven web based assessment services in an E-Learning system has been developed and tested.

The interesting aspect of this model is that it allows the student to initially opt for the DT of the questions soon after he logs into the system of examination. If he opts for the k^{th} DT ($k=1, 2, 3, 4, 5$) the system will start displaying the questions randomly for which the candidate answers. The following is the algorithm covering all the four cases of inputs and contexts:

Case 1: If the candidate answers the first three questions of the k^{th} DT correctly, the system will shift to $k+1^{th}$ DT provided $k \neq 5$. When $k = 5$, the system continues to ask questions from the same level.

Case 2: In case the candidate answers all the three questions of the k^{th} DT incorrectly, the system will shift to $k-1^{th}$ DT provided $k \neq 1$. It follows from the earlier logic the system continues to display from the 1^{st} DT irrespective of the number of wrong answers (WA) provided.

Case 3: This case relates the situation where the examinee answers either one or two questions correctly out of the first three questions from the k^{th} DT. The system exhibits one more question from the same DT. Thus the examinee encounters a total of four questions. A total of three correct answers (CA) shift to $k+1^{th}$ DT, provided $k \neq 5$; otherwise to $k-1^{th}$ DT provided $k \neq 1$.

Case 4: In case examinee answers two questions correctly out of the first four questions from the k^{th} DT, one more question from the same DT is given. A total of three correct answers out of five for the given questions, shifts to $k+1^{th}$ DT; otherwise to $k-1^{th}$ DT. However shifting to a higher or lower DT does not take place when $k=5$ or $k=1$ respectively.

5.1 Evaluation Procedure

The marks for a question in each DT are given in Table1. The table shows that the increment of the marks are corresponding to the DT.

Table 1. Marks associated with each context dimension (DT)

DT	1	2	3	4	5
Mark	0.2	0.4	0.6	0.8	1.0

The maximum marks and the duration of the examination can be set according to the needs of the subject. The test will be terminated either on the expiry of the time frame or when the examinee has attempted questions for

the prescribed maximum marks, whichever occurs first. The score and the number of DT – wise questions asked and answered get displayed at the end of the test.

5.2 Question Bank Creation

A question bank consisting of multiple choice questions for C-Programming language was created by collecting questions from the course experts. A conventional test (where each of the questions in the question bank has to be answered by all the students) was given to a group of students. Calibration was done with the proportion of the examinees who answered each question correctly to the total population, based on which the questions were initially classified into various levels of DT ranging from 1 to 5 (1–very easy and 5 – very difficult) as shown in Table 2.

Table 2. Initial classification of questions into context dimensions (DT)

DT	% Answered Correctly	No. of Questions
5	0 – 10	26
4	11 – 29	80
3	30 – 49	97
2	50 – 69	79
1	70 – 100	78

Each question in the question bank is tagged with a DT. The DT of a question has to be updated periodically, after broad spectrums of students undergo the tests and the question has been asked sufficiently a large number of times.

5.3 Implementation

Application has been developed using PHP software as the front end and MySQL at the back end database server to implement the proposed context aware online adaptation model for knowledge assessment in E-Learning. The test was administered to nearly 500 under graduate and post graduate engineering students. The context dimension, its depth and the adaptation time are noted to determine the performance of the rule rewrite based implementation. The sample code for adaptation in online assessment corresponding to case 1 in the case study is given in Fig 5. The variable correctness_count denotes the number of questions answered correctly in a particular context dimension (DT) and if it is equal to 3 and if the DT level is less than 5, the level of the dimension is incremented.

```

        if($correctness_count=3 && $_SESSION['dt']<5)
        {
            $_SESSION['dt']++;
            $query="update test_log set flag=0 where student_id=" .
$_SESSION['student_id'] . " and
test_date=" . $_SESSION['test_date'] . " and test_id=" . $_SESSION['test_id']
. " and
college_id=" . $_SESSION['college_id'] . """;
            mysql_query($query,$conn);
        }
        ...
        ...
        ...
        header("Location:start_test.php");
        exit;
    }
}

```

Fig. 5. Sample PHP script

The frequent change in the contexts and the corresponding dimension are monitored over the sessions for adaptation rules to be applied as and when needed. The context sensing and switching performance are tabulated as in Table 3. If the user provides a correct answer to a question, the correctness value is set to 1; otherwise to -1. The DT column specifies the difficulty level of the question attempted.

Table 3. Context sensing-switching-closing analysis

Log_id	Session_id	Question_id	Start Time of a question	End Time of the question	Actual Answer of the question	User's Answer	Correctness	DT
40640	09mca50	378	7/2/2011 10:48	7/2/2011 10:52	b	a	-1	1
40641	09mca02	375	7/2/2011 10:49	7/2/2011 10:49	b	c	-1	1
40642	09mca26	18	7/2/2011 10:49	7/2/2011 10:49	a	d	-1	2
40643	09mca27	75	7/2/2011 10:49	7/2/2011 10:49	b	b	1	2

Let τ be the time taken to answer a question. Let t_0 be the start time of the test. The minimum time taken for the 1st adaptation is given by

$$t_0 + 3 \tau \tag{5}$$

But the time taken to answer the question depends both on the knowledge as well as the DT level. Let ψ denote the knowledge level of the candidate. Therefore the time taken to answer a question at DT level i is given by

$$t_i = (DT)_i \psi_i \tau \tag{6}$$

The above equation when considering the maximum allowed three inputs with an average time delay τ becomes,

$$t_0 = (DT)_i \psi_i 3\tau \tag{7}$$

6.0 PERFORMANCE ANALYSIS

Data collected using the online adaptive assessment model in E-Learning system is shown in Table 4. The session in the table starts with the user choosing DT 1 as his choice. The time taken to answer each question and the correctness of the response is monitored. Based on the correctness of the answer, the mark that is corresponding to the DT level of the question is allotted. The total mark is the sum of the marks scored for all the questions in a session.

Table 4. System performance data collected for online adaptation per session

question id	Question Start Time	Question End Time	Actual Answer	User's Answer	Correctness	DT level of the Question	Mark Scored	Time Taken to answer(in seconds)
26	11:07:42	11:07:54	b	b	1	1	0.2	00:12
33	11:07:54	11:08:05	c	c	1	1	0.2	00:11
8	11:08:05	11:08:11	c	c	1	1	0.2	00:06
339	11:08:11	11:09:06	d	d	1	2	0.4	00:55
70	11:09:07	11:09:39	a	a	1	2	0.4	00:32
21	11:09:39	11:09:49	b	c	-1	2	0	00:10
204	11:09:49	11:10:13	c	c	1	2	0.4	00:24
314	11:10:13	11:10:57	a	c	-1	3	0	00:44

268	11:10:57	11:12:03	c	a	-1	3	0	01:06
261	11:12:03	11:14:01	c	c	1	3	0.6	01:58
355	11:14:02	11:14:17	b	d	-1	3	0	00:15
321	11:14:17	11:14:37	a	a	1	2	0.4	00:20
82	11:14:37	11:14:50	d	d	1	2	0.4	00:13
309	11:14:50	11:18:20	a	b	-1	2	0	03:30
18	11:18:20	11:18:32	a	a	1	2	0.4	00:12

The adaptation response over switching between contexts is shown in Table 5. The total mark scored by the candidates, the time taken to complete the test and the average time taken by students to provide a correct/incorrect response to questions at each difficulty level are calculated.

Table 5. Adaptation response on switching context dimension

Session Id.	Total Mark scored (out of 15)	Total Test time(in sec)	DT1		DT2		DT3		DT4		DT5	
			CA Avg Time	WA Avg Time	CA Avg Time	WA Avg Time	CA Avg Time	WA Avg Time	CA Avg Time	WA Avg Time	CA Avg Time	WA Avg Time
09mca01	4.8	1556	9.667	0.000	26.000	110.000	318.000	49.250	0.000	0.000	0.000	0.000
09mca02	12.4	1598	46.430	25.500	15.220	0.000	27.810	31.570	215.000	60.250	0.000	0.000
09mca03	8.4	1999	83.500	45.750	61.250	40.500	39.167	64.667	56.000	139.750	0.000	0.000
09mca04	3.8	1054	7.385	19.455	7.333	13.333	0.000	0.000	0.000	0.000	0.000	0.000
09mca06	7.8	1940	50.000	42.500	116.000	71.000	44.500	99.000	112.333	66.500	0.000	0.000
09mca07	8.4	1885	26.111	0.000	70.111	80.625	38.200	27.667	0.000	50.000	0.000	0.000
09mca08	5.8	897	12.333	25.474	10.143	15.556	0.000	5.667	0.000	0.000	0.000	0.000
09mca09	8.4	2066	44.333	80.000	49.000	48.500	136.667	39.500	64.667	105.000	149.000	0.000
09mca10	1.2	1586	28.500	52.407	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
09mca11	11.2	976	35.667	0.000	28.000	53.000	36.500	29.333	16.667	87.500	53.667	0.000

- CA Avg time – Time taken (in seconds) taken to answer the questions correctly at a DT
- WA Avg time - Time taken (in seconds) taken to answer the questions incorrectly at a DT
- Tot_time - The total time (in seconds) taken to complete the test

The average time taken to answer all the questions correctly by different online users over multiple sessions with different context dimensions are shown in Fig 6.




Fig. 6. Average response time over different DT levels

Basic rules: Rules: $G \rightarrow T$, $T \rightarrow G$, $G \rightarrow A$, $A \rightarrow G$, $G \rightarrow M$, $T \rightarrow D$, $M \rightarrow T$
 (G: Generate, T: Throw Report, A: Award, M: Manage Time, D: Decide)

The performance of the proposed rewrite method over different input patterns in multiple sessions are presented in Table 6.

Table 6. Rule rewrite vs input pattern

Session/ Roll No.	Test Start time	Test End time	DT in the answering pattern	Total Test Time (in sec)	Rules Rewriting Time (in sec)	No. of Rules rewritten
S1/09mca01	11:07:42	11:33:40	1-2-3-2-3	1556	29	8
S2/09mca02	10:49:21	11:16:53	1-2-3-2-3-4-3-2-3	1598	147	19
S3/09mca03	10:50:32	11:23:53	1-2-3-4-3-4	1999	197	18
S4/09mca04	10:51:20	11:08:51	1-2-1-2-1	1054	182	26
S5/09mca06	10:50:13	11:22:35	1-2-3-4-3-4	1940	250	17
S6/09mca07	10:52:43	11:24:14	1-2-1-2-3-2-3-2-3-4	1885	43	16
S7/09mca08	10:52:51	11:07:49	1-2-1-2-1-2-3-2-1	897	210	22
S8/09mca09	10:51:37	11:26:04	1-2-1-2-3-4-5-4	2066	180	15
S9/09mca10	11:18:01	11:34:24	1	1586	1586	19
S10/09mca11	10:50:12	11:06:29	1-2-3-2-3-4-5	976	61	11

The adaptation time and rule rewrite time are shown in Fig 7 and Fig 8 respectively.




Fig.7. Adaptation time over multiple sessions




Fig. 8. Time for rules rewriting

7.0 CONCLUSION

A context aware distributed online adaptation model for knowledge assessment in an E-Learning system is proposed with its framework as a middleware component. The context variables and their functional mappings with their various dimensions are considered in designing the system. The context sensing and switching actions have been carried out by considering the runtime policies in the rule based rewriting sub system. The current standards, regulations, and risks along with the various policies are taken into account as the input to the adaptation manager component. The needed interfaces are declared and deployed to inform and generate the computational rules for the system. The context awareness has been incorporated as a set of multiple rules which are to be rewritten not only when the end user changes his or her input as a content driven but also when the system average response time elapses as a time triggered application. The performance of the model is enhanced by carefully generating rules at run time which are based on the user as well as the system that triggers a switching during adaptation phase. The online assessment is computationally modeled with an automaton to make it adaptable based on the major external policy changes. A case study has been carried out to implement the proposed framework components for nearly 500 Engineering students in an institution and the middleware was deployed to monitor the context changes and the adaptation time over multiple sessions. The application which is an information processing and decision making component dynamically interacts with the time management and session allocation modules written in PHP as the user end with multiple databases in MySQL at the backend.

The system performance in terms of its functionality and the adaptation capability in terms of numbers of rules generated and rewritten are shown. From the observations, it is found that a student who has completed the entire assessment within 897 seconds in which the first context switching comes at 210 seconds where a total of 22 rules have been rewritten. In another scenario, only 8 rules have been rewritten for a total session time of 1556 seconds out of which 29 seconds as system rewrite time. It has been inferred from the performance charts that the system behaves non-linearly with respect to the total session time and rules rewrite time because of the laziness and eagerness of the individual student in answering the questions.

The proposed work is to be extended to all the departments as contexts and covering different subject domains as dimensions for more number of students in future. The limitation of the proposed is the synchronization issues when system crashes. The high availability and secured transmission of answers over the distributed network are the next challenges in the future work. The online question creation, and information transmission after identity management are some of the limitations in the case of large scale deployment in an educational data grid environment. The same work can also be deployed as a number of virtual services with all key process activities and virtual networks with virtual resources like hardware and software as services as an Exam-In-Cloud mission in future.

REFERENCES

- [1] Anind K Dey, "Understanding and Using Context", *Journal of Personal Ubiquitous Computing*, 2001, pp. 4 - 7.
- [2] Bradley C.Love , Matt Jones, Marc T .Tomlinson & Michael Howe, " Learning to Predict Information Needs : Context-Aware Display as a Cognitive Aid and an Assessment Tool", *Proceedings of the 27th International Conference on Human factors in Computing Systems*, 2009, pp. 1351- 1360.
- [3] Jane Yau & Mike Joy, "A Context-aware and Adaptive Learning Schedule Framework for Supporting Learners' Daily Routines", *Second International Workshop on Mobile Communications and Learning (MCL 2007)*, Sainte-Luce, Martinique, 2007, pp.31.
- [4] Tarak Chaari & Frederique Laforest, "Adaptation in Context Aware Pervasive Information Systems: The SECAS Project", *Journal of Pervasive Computing and Communications*, June 2006, pp.400 – 425.
- [5] Anders Kofod-Petersen & Marius Mikalsen, "An Architecture supporting Implementation of Context – Aware Services", *Workshop on Context Awareness for Proactive Systems*, 2005, pp. 31-42.
- [6] Wei Li, "A Service - Oriented SIP Infrastructure for Adaptive and Context –Aware Wireless Services", *Proceedings of the 2nd International Conference on Mobile and Ubiquitous Multimedia*, 2003, pp. 81-88.
- [7] Mahmoud Hussein, Jun Han & Alan Colman, "Integrated Modelling of Context-Aware Adaptive Software Systems, Technical Report, *Faculty of Information & Communication Technologies*, Swinburne University of Technology, Australia, 2010.
- [8] Mare Dalmau, Philippe Roose & Sophie Laplace, "Context Aware Adaptable Applications – A Global Approach", *International Journal of Computer Science*, 2009, pp. 13 – 23.
- [9] Davy Peuveneers & Yolande Bebes, "Adaptive Context Management using a Component Based Approach", *International Federation for Information Processing*, 2005, pp. 14-26.
- [10] Liliana Ardissono , Robet Furnai, Anna Guy, Giovanna Petroni & Maino Segnan, " A Framework for the Management of Context Aware Workflow Systems", *Third International Conference on Web Information Systems & Technologies* , 2007, pp. 80-87.
- [11] R.G. Raj and S. Abdul-Kareem. "A Pattern Based Approach for the Derivation of Base Forms of Verbs from Participles and Tenses for Flexible NLP". *Malaysian Journal of Computer Science*, 2011, 24(2): 63 – 72.
- [12] Economides.A.A, "Adaptive Context-Aware Pervasive and Ubiquitous Learning", *International Journal of Technology Enhanced Learning*, 2009, pp. 169-192.
- [13] Economides.A.A, "Adaptive Orientation Methods in Computer Adaptive Testing ", Griff Richards (ed.) *Proceedings E-Learn 2005 World Conference on E-Learning in Corporate, Government, Healthcare and Higher Education*, , Canada, 2005. pp. 1290-1295.
- [14] Lamboudis.D & Economides.A.A, " Adaptive Exploration of User Knowledge in Computer based Testing", *Proceedings of the sixth International Conference on TELEINFO- Telecommunication Systems and Computer Science, Cancun, Mexico*, 2004. pp. 322-327
- [15] Jane Yau & Mike Joy, "Architecture of a Context-aware and Adaptive Learning Schedule for Learning Java", "*Seventh IEEE International Conference on Advanced Learning Technologies (CALT)*" , 2007, pp. 252-256.
- [16] R.G. Raj, V. Balakrishnan. "A Model for Determining The Degree of Contradictions in Information". *Malaysian Journal of Computer Science*, 2011, 24(3): 160 – 167.

BIOGRAPHY

V.GEETHA is currently working as Associate Professor and has a teaching experience of 20 years. She is currently pursuing PhD under Anna University, Chennai. Her research interests include Knowledge Management and Data Mining.

Dr. CHANDRASEKARAN SUBRAMANIAM is currently working as a Professor and has been in teaching and research for more than 30 years and was awarded PhD from Anna University, Chennai in the area of Fault Tolerant Computing Systems. His research interests are Context Aware Computing, Rewrite based Computing and Formal Verification of Computing system. He is an active member in IEEE, ACM, IET, ASQ, SEI and WSEAS.

Dr.R.NADARAJAN is Professor and Head of the Department of Mathematics and Computer Applications, PSG College of Technology, India. He obtained his PhD degree from Annamalai University, India. He is the author of over 30 journal papers, as well as numerous proceeding papers and technical reports. He has been a reviewer for many Journals. His research interests include Object Computing, Data Mining and Database Technologies. He is the Chairman, Computer Society of India Coimbatore chapter. Member of Operational Research Society of India and ISTE (Indian Society for Technical Education).

G.S.NANDAKUMAR is currently working as Associate Professor and has a teaching experience of 14 years. He is currently pursuing PhD under Anna University, Coimbatore. His research interests include Knowledge Management, Software Engineering and Data Mining.